

## SKB 11-13 RG11 Coaxial cable CATV | SAT



- ✓ 3-way shielded
- ✓ Class A++ according to EN 50117-2-3
- ✓ Screening factor  $\geq 105$  dB @ 30...1000 MHz
- ✓ Coupling resistance  $\leq 0,9$  m $\Omega$ /m @ 5...30 MHz
- ✓ Inner conductor made of solid copper, diameter 1,63 mm
- ✓ Physically-foamed dielectric, diameter 7,4 mm
- ✓ Screening alum. foil, tinned copper braiding, alum. foil
- ✓ Jacket PE, black
- ✓ UV resistant
- ✓ Degressive metering
- ✓ Fire behavior Fca acc. to EN 50575
- ✓ Suitable for underground installation in a ductwork for cables
- ✓ 300 m on wooden drum
- ✓ Compression plug, compression tool and stripping tool available on request.

### Order information

Type	SKB 11-13
Order no.	SKB01113
GTIN	7611682007756
PE	1
VE	1
EU customs tariff number	85442000



### Technical data

#### Electrical data

Impedance	75 Ohm
Attenuation	5,4 dB / 100 m @ 200 MHz 13,5 dB / 100 m @ 1000 MHz 22,0 dB / 100 m @ 2400 MHz
Screening factor	>105 dB @ 30...1000 MHz >95 dB @ 1000...2000 MHz >85 dB @ 2000...3000 MHz
Coupling resistance	<0,9 m $\Omega$ /m @ 5...30 MHz

#### Mechanical data

Inner conductor diameter	Cu, 1,63 mm
Dielectric diameter	7,3 mm
Braiding   opt. coverage	144 x 0,15 mm   85%
Jacket diameter	10,3 mm
Bending radius single   multiple	36   100 mm

#### General

Application temperature range	-5...+50°C
Operating temperature range	-40° C ... +85° C
Fire behavior	Fca

### Suitable products

[CFS 7-00 F | male crimp type](#)

[CFS 7-02 F | male screw type](#)