

SKB 94-01 Coaxial cable | 3-way shielded | 100 m



- ✓ For SAT or CATV indoor installation
- ✓ Vodafone listed
- ✓ According to KDG 1 TS 153
- ✓ Class A+ according to EN 50117-2-4
- ✓ Fire behaviour Eca acc. to EN 50575
- ✓ Inner conductor Cu, diameter 1.02 mm
- ✓ Physically-foamed dielectric, diameter 4.6 mm
- ✓ Screening aluminium foil, bonded/tinned copper braiding/aluminium foil
- ✓ Jacket PVC, white
- ✓ UV resistant
- ✓ Degressive metering
- ✓ 100 m on a cardboard spool

Order information

| | |
|--------------------------|---------------|
| Type | SKB 94-01 |
| Order no. | SKB09401 |
| GTIN | 7611682004021 |
| PE | 1 |
| VE | 4 |
| EU customs tariff number | 85442000 |



Technical data

Electrical data

| | |
|---------------------|---|
| Impedance | 75 Ω |
| Attenuation | 8.7 dB / 100 m @ 200 MHz 18.4 dB / 100 m @ 800 MHz 33.2 dB / 100 m @ 2400 MHz |
| Screening factor | ≥110 dB @ 30...1000 MHz ≥110 dB @ 1000...2000 MHz ≥110 dB @ 2000...3000 MHz |
| Coupling resistance | <1.5 mOhm/m |

Mechanical data

| | |
|--|--------------------|
| Inner conductor material diameter | Cu 1.02 mm |
| Dielectric diameter | 4.60 mm |
| Dielectric diameter, incl. bonded foil | 4.70 mm |
| Braiding opt. coverage | 120 x 0.1 mm 65% |
| Jacket material diameter | PVC 6.60 mm |
| Bending radius single multiple | 24 mm 68 mm |

General

| | |
|-------------------------------|-------------|
| Application temperature range | -5...+50°C |
| Operating temperature range | -20...+75°C |
| Fire behaviour | Eca |
| Weight | 4.500 kg |

Suitable products

- [SKA 1-00 Cable dispenser](#)
- [CKS 7-48 IEC | male | compression](#)
- [CKK 7-48 IEC | female | compression](#)
- [CFS 97-48 F | male | compression](#)
- [CFS 99-48 F | male | compression | Quickfix](#)
- [CFS 100-48 F | male | compression | Quickfix](#)
- [CFS 93-48 F | Opti-fix | male | self compression](#)
- [SZU 11-01 Water protection sleeve](#)