Di@na is a carefully designed antenna, which construction cares even the smallest details, maintaining the symmetry in all components that minimizes internal reflections and maximize performance.

APPLICATION

Digital and analogue TV reception.


CHARACTERISTICS


- Pre-assembled for easy set-up.
- The reflector and dipole have been designed for a higher front-to-back ratio.
- Long-life antenna due to its aluminium and ABS plastic construction.
- Ergonomic design for a tool-free installation.
- Suitable for horizontally or vertically polarised channels, maintaining its waterresistance in any position.


 It has an "F" connector with protection cover.
- In case of low coverage areas, the Di@na @ktive model incorporates a dipole that improves the reception margin in the installation.

















Supply voltage	12 ÷ 24 Vdc
Current drawn	25 mA

				Garrotte aratti	20 \	
MODEL		Di@na	Di@na 6U	Di@na @ktive	Di@na @ktive 6U	
Reference		84375	84377	84387	84386	
Channels		21 69				
Gain		16,5		32		
Impedance	Ω	75				
Return losses	dB	15				
Horizontal opening angle a -3dB	•∤	33				
Length	mm	1.128				
Windload 130 km/h 160 km/h	N	71 98				
Units per package		1	6	1	6	
Packing Dimensions	mm	740 x 330 x 180	760 x 340 x 660	740 x 330 x 180	760 x 340 x 660	
Weight		2	12	2	12	

GAIN RESPONSE



HORIZONTAL OPENING DIAGRAM

